

## RF EYE NODE 40-8

# INTELLIGENT WIDEBAND RECEIVER

The RFeye Node 40-8 offers class-leading RF performance for advanced capability, real-time spectrum operations or deployment on any spectrum critical site.

The RFeye Node 40-8 uses the latest superheterodyne receiver technology to provide outstanding quality and performance at a competitive price. It is a complete spectrum monitoring and geolocation system designed for remote deployment in distributed networks both indoors and outdoors, including in hostile environments. Packaged in a compact, rugged and weatherproof housing, it has been optimized for size, weight and power (SWaP) and is simple to connect to power and network.

The Node 40-8 is characterized by outstanding noise figure, channel re-tune time and spurious free dynamic range parameters, well above any other product in its class. It also offers all of the multi-mission capability of the RFeye product range allowing multiple concurrent measurements and geolocations to be performed and multiple users to connect simultaneously from remote locations.



# 40-8 SPECIFICATIONS



## Single channel receiver

Switchable RF inputs 4 x SMA connectors

## Frequency

Range 9 kHz to 8 GHz

## Noise figures at maximum sensitivity

9 kHz to 0.1 GHz 10 dB typical

0.1 GHz to 2.4 GHz 6 dB typical

2.4 GHz to 6 GHz 7 dB typical

6 GHz to 8 GHz 8 dB typical

## Phase noise

Receiver input at 1 GHz -110 dBc/Hz at 20 kHz offset, typ.

Receiver input at 8 GHz -100 dBc/Hz at 20 kHz offset, typ.

## Signal analysis

Instantaneous bandwidth 40 MHz

Tuning resolution 1 Hz

## Internal frequency reference

Stability over temperature  $\pm 0.5$  ppm

Ageing  $\pm 3$  ppm

## Programmable sweep modes

Sweep speed at 2 MHz RBW 245 GHz/s typ.

User programmable modes free run continuous, single timed, user trigger and adaptive

Trigger-on-event modes user defined masks, actions and alarms

## Sampling

Rate 62.5 MS/s I&Q

## Local oscillator emissions

Re-radiation  $\leq -90$  dBm typical

## Frequency references

Selectable Internal, GNSS or external

External input 10 MHz  $\pm 10$ ppm

## Location & Timing

GNSS device (standard) GPS, GLONASS, Galileo

GNSS timing accuracy  $< 20$  ns

## Processor sub-system

CPU Intel E3845 quad core

## I/O

Network 1 x 1 GigE, with POnE

Universal Serial Bus 1 x USB3.0, 1 x USB2.0

2 x IEEE1394 expansion ports 2 x SyncLinc ext peripheral control

GNSS antenna input 1 x SMA passive or active (3.3 VDC)

## Data storage

External SSD (optional) via USB interfaces

## System software

Boot firmware BIOS

Operating system Linux, kernel v 2.6

RFeye Node Control Protocol NCP Server (NCPd)

Node Apps (optional) Logger, EMP, Detectors

## Size, weight and power

Dimensions (Node only) (w, h, d) 200 x 50 x 130 mm (7.9 x 2.0 x 5.1 inches)

Dimensions (w. end plates & heatsink) 200 x 74 x 330 mm (7.9 x 3.0 x 13 inches)

Weight (Node only) 2.1 kg (5 lbs)

Weight (w. end plates & heatsink) 4.5 kg (10.7 lbs)

DC power 12 VDC (max limit 30V)

POnE 56 VDC

## Power consumption

Typical 20 W

Maximum 25 W

## Environmental

Operating temperature -30 to +55 °C (-22 to 131°F)

Storage temperature -40 to +71 °C (-40 to 160°F)

Ingress protection IP67 (w. optional end plates)



**CRFS Inc**  
Chantilly,  
VA, USA  
+1 571 321 5470

**CRFS Ltd**  
Cambridge,  
United Kingdom  
+44 (0) 1223 859 500

CRFS and RFeye are trademarks or registered trademarks of CRFS Limited. Copyright © 2023 CRFS Limited. All rights reserved. No part of this document may be reproduced or distributed in any manner without the prior written consent of CRFS. The information and statements provided in this document are for informational purposes only and are subject to change without notice.



UK Certificate number: FS576625