

## RFEYE SENS PORTABLE

# LIGHTWEIGHT MOBILE I/Q RECORDER

Compact RF digital recording solution  
for capture and analysis of RF signals

The SenS Portable recorder provides real-time spectrum analysis and long-duration recording capabilities in a compact, low-power, portable configuration. With built-in high-speed, solid-state memory of up to 25.6 TB, SenS interfaces to the Thunderbolt port of a desktop or laptop PC for seamless integration with the RFeye DeepView signal extraction and analysis software.

### FEATURES

- 9 kHz to 8, 18 or 40 GHz frequency range for C, X, Ku, Ka bands and 5G recording
- Integrated SSD(s) for 12+ hours of recording time at 100 MHz IBW
- Can be powered by vehicle AC inverter
- Low SWaP for signal recording on the move
- Powerful visualization and analysis tools
- Time and frequency filtering to minimize file size of I/Q exports

### APPLICATIONS

- Portable signal collection – record native RF environments outside of a lab
- Anechoic chambers – extract and test target signals with forensic DeepView software
- Stimulus/response system development – capture signal files with crystal-clear fidelity for digital manipulation and playback



# SENS PORTABLE



## System components

### Internal receiver: R-8 option

#### Frequency

Range	9 kHz to 8 GHz
-------	----------------

#### Noise figures at maximum sensitivity

9 kHz to 0.1 GHz	10 dB typical
0.1 GHz to 2.4 GHz	6 dB typical
2.4 GHz to 6 GHz	7 dB typical
6 GHz to 8 GHz	8 dB typical

#### Sweep speed

Sweep speed at 2 MHz RBW	280 GHz/s typical
--------------------------	-------------------

### Internal receiver: R-18 option

#### Frequency

Range	9 kHz to 18 GHz
-------	-----------------

#### Noise figures at maximum sensitivity

9 kHz to 83 MHz	11 dB
83 MHz to 1 GHz	9 dB
1 GHz to 2.9 GHz	8 dB
2.9 GHz to 5.9 GHz	7 dB
5.9 GHz to 10 GHz	9.5 dB
10 GHz to 15 GHz	12 dB
15 GHz to 16 GHz	13 dB
16 GHz to 17 GHz	18 dB
17 GHz to 18 GHz	21 dB

#### Sweep speed

Sweep speed at 2 MHz RBW	390 GHz/s typical
--------------------------	-------------------

### Internal receiver: R-40 option

#### Frequency

Range	9 kHz to 40 GHz
-------	-----------------

#### Noise figures at maximum sensitivity

9 kHz to 0.12 GHz	12 dB typical
0.12 GHz to 6 GHz	8.5 dB typical
6 GHz to 10 GHz	10.5 dB typical
10 GHz to 18 GHz	13 dB typical
18 GHz to 40 GHz	16 dB typical

## Storage and record times

Disc capacity	25 MHz IBW	50 MHz IBW	100 MHz IBW
6.4 TB	12:10	06:05	03:02
12.8 TB	24:20	12:10	06:05
19.2 TB (R8 & R18 only)	36:30	18:15	09:07
25.6 TB (R8 & R18 only)	48:40	24:20	12:10



RFeye DeepView software is the ultimate signal extraction tool. Its robust indexing feature allows users to sift through multi-terabyte datasets and quickly find and export signals of interest.

### Signal analysis software

RFeye DeepView (included)	Windows 10 based; 4-lane Thunderbolt 3 port required for hardware
---------------------------	--

### Overall system

#### Signal analysis

Switchable full-bandwidth RF inputs	3 x SMA connectors (R-40 - 2 x SMA, 1 x K2.92)
Instantaneous bandwidth	100 MHz
Tuning resolution	1 Hz

#### Sampling

Resolution	16 bits I&Q
Rate	125 MS/s I&Q

#### Internal frequency reference

Initial accuracy @ 20°C	±0.1ppm typical
Stability over temperature	±0.3 ppm typical
Ageing over 1 day	±0.04 ppm per year

#### Connectivity USB-C (Thunderbolt 3)

Equivalent lanes	4 x Gen 2.0 PCIe
Total throughput	Up to 40 Gbps

#### Size, Weight and Power

Dimensions (w, h, d)	10.9 x 5.0 x 6.5 in 277 x 126 x 165 mm
Weight (w/ dual SSDs)	7 lbs 6 oz/ 3.4 kg
Power consumption	60 W typical

#### Environmental

Operating temperature range	0 to +50°C (32 to 122°F)
Storage temperature range	-40 to +70°C (-40 to 158°F)



**CRFS Inc**  
Chantilly,  
VA, USA  
+1 571 321 5470

**CRFS Ltd**  
Cambridge,  
United Kingdom  
+44 (0) 1223 859 500

CRFS and RFeye are trademarks or registered trademarks of CRFS Limited. Copyright © 2023 CRFS Limited. All rights reserved. No part of this document may be reproduced or distributed in any manner without the prior written consent of CRFS. The information and statements provided in this document are for informational purposes only and are subject to change without notice.



UK Certificate number: FS576625